

# Extract Reference File

*This chapter provides record formats which allow Automated Commercial System (ACS) users to query antidumping/countervailing duty data, codes, gold prices, currency, team assignments, and tariff data required on certain ACS records.*

- ANTIDUMPING/COUNTERVAILING DUTY FILE.....ERF-6**  
The Antidumping/Countervailing Duty File provides detailed data relating to antidumping/countervailing duty cases.
- REGION/DISTRICT/PORT CODE FILE .....ERF-7**  
The Region/District/Port Code File identifies each region/district/port of the U.S. Customs and Border Protection (CBP).
- COUNTRY CODE FILE ... .....ERF-7**  
The Country Code File contains the International Organization for Standardization (ISO) country codes.
- FOREIGN PORT CODE FILE .....ERF-8**  
The Foreign Port Code File provides the codes assigned to foreign ports.
- ZIP CODE AND STATE CODE FILE .....ERF-8**  
The ZIP Code and State Code File provides territory and state codes.
- CARRIER CODE FILE .....ERF-8**  
The Carrier Code File provides data pertaining to air and vessel carriers.
- GOLD PRICE .....ERF-9**  
The Gold Price File provides data on the current price of gold.
- CURRENCY QUERY FILE .....ERF-9**  
The Currency Query File provides currency exchange rates for a specific period of time.
- CURRENCY CONVERSION FILE .....ERF-9**  
The Currency Conversion File converts foreign dollars into U.S. dollars.
- HARMONIZED TARIFF SCHEDULE FILE .....ERF-10**  
The Harmonized Tariff Schedule File provides the classification number of goods imported into the United States.

**FACILITIES INFORMATION AND RESOURCES MANAGEMENT SYSTEM**

**(FIRMS) CODE .....ERF-10**

The Facilities Information and Resources Management System (FIRMS) code identifies the CBP facility where the goods are located.

**IMPORT SPECIALIST TEAM ASSIGNMENT FILE...ERF-10**

The Import Specialist Team Assignment File provides the team number of the import specialist assigned to the merchandise for a specific district/port.

**RECORD DESCRIPTIONS**

**Record Identifier C1 (Input).....ERF-12**

A mandatory antidumping/countervailing duty case query input record that allows antidumping/countervailing duty data to be queried by country and status.

**Record Identifier C2 (Output).....ERF-13**

A mandatory antidumping/countervailing duty case query output record that is identical to the C1 input record.

**Record Identifier C3 (Output).....ERF-14**

A conditional antidumping/countervailing duty query output record that provides data pertaining to the International Organization for Standardization (ISO) country code, case number, related case number, manufacturer identification (ID) number, shipper ID, case status, case status date, and bond/cash indicator.

**Record Identifier C4 (Output).....ERF-16**

A conditional antidumping/countervailing duty query output record that provides data pertaining to the case number, contact, phone, liquidation/suspension date, and short description.

**Record Identifier C5 (Output).....ERF-17**

A conditional antidumping/countervailing duty query output record that provides data pertaining to the case number, rate indicator, deposit rate, effective entry and export date, and bond/case indicator.

**Record Identifier C6 (Output).....ERF-19**

A conditional antidumping/countervailing duty query output record that provides data pertaining to up to seven tariff numbers associated with the case.

**Record Identifier C7 (Output).....ERF-20**

A conditional antidumping/countervailing duty query output record that provides data pertaining to the case number and manufacturer name.

**Record Identifier C8 (Output).....ERF-21**

A conditional antidumping/countervailing duty query output record that provides data pertaining to the case number and shipper.

**Record Identifier C9 (Output).....ERF-22**

A conditional antidumping/countervailing duty query output record that provides an error message.

**Record Identifier F101 (Input).....ERF-23**

A mandatory region/district/port input record that provides data pertaining to the reference file code for the Region/District/Port Code File.

- Record Identifier F101 (Output)**.....**ERF-24**  
A mandatory region/district/port output record that provides data pertaining to the reference file code, region/district/port code, name, address, and carrier type.
- Record Identifier F201 (Output)**.....**ERF-26**  
A mandatory region/district/port output record that provides data pertaining to the reference file code, region/district/port code and address.
- Record Identifier F301 (Output)**.....**ERF-27**  
A mandatory region/district/port output record that provides data pertaining to the reference file code, district/port code, city, state, and ZIP code.
- Record Identifier F401 (Output)**.....**ERF-28**  
A conditional region/district/port output record that provides data pertaining to the reference file code, region/district/port code and subport code.
- Record Identifier F102 (Input)**.....**ERF-29**  
A mandatory Country Code File input record that provides data pertaining to the reference file code.
- Record Identifier F102 (Output)**.....**ERF-30**  
A mandatory Country Code File output record that provides data pertaining to the reference file code, country, rate column indicator, restriction indicator, Generalized System of Preferences (GSP) indicator, begin and end date, special programs indicator, country name, and currency name and code.
- Record Identifier F202 (Output)**.....**ERF-33**  
A conditional country code output record that provides data pertaining to a country, rate of duty, restriction indicators and special program indicators.
- Record Identifier F104 (Input)**.....**ERF-37**  
A mandatory port code input record that provides data pertaining to the reference file code for the Foreign Port file.
- Record Identifier F104 (Output)**.....**ERF-38**  
A mandatory port code output record that provides data pertaining to the reference file code, port of lading code, and port of lading name.
- Record Identifier F105 (Input)**.....**ERF-39**  
A mandatory input record that provides data pertaining to the reference file code for the ZIP code and state code file.
- Record Identifier F105 (Output)**.....**ERF-40**  
A mandatory ZIP and state code output record that provides data pertaining to the reference file code, ZIP code range, and state code.
- Record Identifier F106 (Input)**.....**ERF-41**  
A mandatory carrier input record that provides data pertaining to the reference file code for the Carrier Code file.
- Record Identifier F106 (Output)**.....**ERF-42**  
A mandatory Carrier Code File output record that provides data pertaining to the reference file code, vessel carrier name, carrier code and carrier mode of transportation codes, address, and air waybill prefix.
- Record Identifier F107 (Input)**.....**ERF-44**  
A mandatory gold price input record that provides data pertaining to the reference file code and gold price date.

- Record Identifier F107 (Output)**.....ERF-45  
A mandatory gold price output record that provides data pertaining to the reference file code, gold price date, gold price, and narrative message.
- Record Identifier F108 (Input)**.....ERF-46  
A mandatory currency query input record that provides data pertaining to the reference file code, International Organization for Standardization (ISO) country code, ISO currency code, and the beginning and ending exchange rate dates.
- Record Identifier F108 (Output)**.....ERF-47  
A mandatory currency query output record that provides data pertaining to the reference file code, query results code, and the beginning and ending exchange rate dates, exchange rates, and indicator.
- Record Identifier F208 (Output)**.....ERF-49  
A conditional currency query output record that provides data pertaining to the reference file code, International Organization for Standardization (ISO) country code, exchange rate date, exchange rate (2 and 3), and indicator (2 and 3).
- Record Identifier F109 (Input)**.....ERF-50  
A mandatory currency conversion query input record that provides data pertaining to the reference file code, International Organization for Standardization (ISO) country code, ISO currency code, exchange rate date and foreign currency amount.
- Record Identifier F109 (Output)**.....ERF-51  
A mandatory currency conversion query output record that provides data pertaining to the reference file code, International Organization for Standardization (ISO) country code, ISO currency code, exchange rate date, query results code and up to three exchange rates, indicators, and equivalent dollar amounts.
- Record Identifier F209 (Output)**.....ERF-53  
A conditional currency conversion query output record that provides data pertaining to the reference file code, International Organization for Standardization (ISO) country code, exchange rate date, remarks, and a narrative message. Results are received only for the date used on input.
- Record Identifier F110 (Input)**.....ERF-54  
A mandatory input record that requests update data for a range of Harmonized Tariff Schedule numbers.
- Record Identifier F110 (Output)**.....ERF-55  
A mandatory output extract reference file that provides data for a range of Harmonized Tariff Schedule numbers and a narrative message.
- Record Identifier F111 (Input)**.....ERF-56  
A mandatory location of goods (FIRMS) file input record that provides data pertaining to the reference file code, FIRMS code, name of facility, and district code.
- Record Identifier F211 (Output)**.....ERF-58  
A conditional location of goods (FIRMS) output record that provides data pertaining to the reference file code, district/port code, FIRMS code, status, facility type and name of the facility.
- Record Identifier F311 (Output)**.....ERF-59  
A conditional location of goods (FIRMS) file output record that provides data pertaining to the reference file code, facility address, city and state.
- Record Identifier F411 (Output)**.....ERF-60  
A mandatory location of goods (FIRMS) file output record that provides data pertaining to the ZIP code, country, error code and error message.

**Record Identifier F112 (Input)**.....**ERF-61**  
A conditional input record to query the import specialist team assignment file.

**Record Identifier F112 (Output)**.....**ERF-62**  
A conditional output record that provides data pertaining to the import specialist team assignment file.

## **Extract Reference File**

Extract reference files provide up-to-date data on:

- Antidumping/Countervailing Duty Cases
- Carrier Codes
- Country Codes
- Currency Conversion Codes
- Currency Queries
- Facilities Information and Resources Management System (FIRMS) Codes
- Foreign Port Codes
- Gold Prices
- Harmonized Tariff Schedule
- Import Specialist Team Assignment
- Region/District/Port Codes
- ZIP Codes and State Codes

Extract reference files are useful for editing and cross-referencing input data. The U.S. Customs and Border Protection (CBP) notifies Automated Commercial System (ACS) users, by administrative message or other means, when an update has been made to a file. This allows users to update their own files.

### **Antidumping/Countervailing Duty File**

The Antidumping/Countervailing Duty File contains data relating to antidumping/ countervailing duty cases and can be queried for a specific country or all countries.

ACS users can also query the Antidumping/Countervailing Duty File by a specific country, tariff number, or case number using the Antidumping/Countervailing Duty Query capability. For additional information on the antidumping/countervailing duty query capability, refer to the Antidumping/ Countervailing Duty Query chapter in this document.

**Input:** Record Identifier C1 is a mandatory antidumping/countervailing duty query input record.

The application identifier on Record Identifier B is IP. For additional information on Record Identifier B, refer to the Application Control chapter of this document.

**Output:** Record Identifier C2 is a mandatory antidumping/countervailing duty query output record. Record Identifiers C3 through C9 are conditional antidumping/countervailing duty query output records.

The application identifier on Record Identifier B is IT. For additional information on Record Identifier B, refer to the Application Control chapter of this document.

## **Region/District/Port Code File**

The Region/District/Port Code File identifies each region/district/port of CBP.

**Input:** Record Identifier F101 is a mandatory region/district/port code input record.

The application identifier on Record Identifier B is FI. For additional information on Record Identifier B, refer to the Application Control chapter of this document.

**Output:** Record Identifiers F101, F201, and F301 are mandatory region/district/port records. Record Identifier F401 is conditional.

The application identifier on Record Identifier B is FR. For additional information on Record Identifier B, refer to the Application Control chapter of this document.

## **Country Code File**

International Organization for Standardization (ISO) country codes are contained in the Country Code File.

**Input:** Record Identifier F102 is a mandatory Country Code File record.

The application identifier on Record Identifier B is FI. For additional information on Record Identifier B, refer to the Application Control chapter of this document.

**Output:** Record Identifier F102 is a mandatory Country Code File record.

The application identifier on Record Identifier B is FR. For additional information on Record Identifier B, refer to the Application Control chapter of this document.

## **Foreign Port Code File**

The Foreign Port Code file provides the codes assigned to foreign ports.

***Input:*** Record Identifier F104 is a mandatory foreign port code record.

The application identifier on Record Identifier B is FI. For additional information on Record Identifier B, refer to the Application Control chapter of this document.

***Output:*** Record Identifier F104 is a mandatory port code record.

The application identifier on Record Identifier B is FR. For additional information on Record Identifier B, refer to the Application Control chapter of this document.

## **ZIP Code and State Code File**

The ZIP Code and State Code File provides territory and state codes.

***Input:*** Record Identifier F105 is a mandatory ZIP code and state code record.

The application identifier on Record Identifier B is FI. For additional information on Record Identifier B, refer to the Application Control chapter of this document.

***Output:*** Record Identifier F105 is a mandatory ZIP and state code record.

The application identifier on Record Identifier B is FR. For additional information on Record Identifier B, refer to the Application Control chapter of this document.

## **Carrier Code File**

The Carrier Code File provides data pertaining to air and vessel carriers.

***Input:*** Record Identifier F106 is a mandatory Carrier Code File record.

The application identifier on Record Identifier B is FI. For additional information on Record Identifier B, refer to the Application Control chapter of this document.

***Output:*** Record Identifier F106 is a mandatory Carrier Code File record.

The application identifier on Record Identifier B is FR. For additional information on Record Identifier B, refer to the Application Control chapter of this document.



## **Gold Price File**

The Gold Price File provides data on the price of gold.

**Input:** Record Identifier F107 is a mandatory gold price record.

The application identifier on Record Identifier B is FI. For additional information on Record Identifier B, refer to the Application Control chapter of this document.

**Output:** Record Identifier F107 is a mandatory gold price record.

The application identifier on Record Identifier B is FR. For additional information on Record Identifier B, refer to the Application Control chapter of this document.

## **Currency Query File**

The Currency Query File provides currency exchange rates for a certain period of time.

**Input:** Record Identifier F108 is a mandatory currency query record.

The application identifier on Record Identifier B is FI. For additional information on Record Identifier B, refer to the Application Control chapter of this document.

**Output:** Record Identifier F108 is a mandatory currency query record and Record Identifier F208 is a conditional currency query record.

The application identifier on Record Identifier B is FR. For additional information on Record Identifier B, refer to the Application Control chapter of this document.

## **Currency Conversion File**

The Currency Conversion File converts foreign dollars into U.S. dollars.

**Input:** Record Identifier F109 is a mandatory currency conversion query record.

The application identifier on Record Identifier B is FI. For additional information on Record Identifier B, refer to the Application Control chapter of this document.

**Output:** Record Identifier F109 is a mandatory currency conversion query record and Record Identifier F209 is a conditional currency conversion query record.

The application identifier on Record Identifier B is FR. For additional information on Record Identifier B, refer to the Application Control chapter of this document.

## **Harmonized Tariff Schedule File**

The Harmonized Tariff Schedule File provides the classification number of goods imported into the United States.

**Input:** Record Identifier F110 is a mandatory Harmonized Tariff Schedule record.

The application identifier on Record Identifier B is FI. For additional information on Record Identifier B, refer to the Application Control chapter of this document.

**Output:** Record Identifier F110 is a mandatory Harmonized Tariff Schedule record.

The application identifier on Record Identifier B is FR. For additional information on Record Identifier B, refer to the Application Control chapter of this document.

**Note:** Record Identifier F110 (Input) and F110 (Output) are also included in the Harmonized Tariff Schedule chapter of this document.

### **Facilities Information and Resources Management System (FIRMS) Code**

The Facilities Information and Resources Management System (FIRMS) Code identifies the CBP facility where the goods are located.

**Input:** Record Identifier F111 is a mandatory location of goods (FIRMS) record.

The application identifier on Record Identifier B is FI. For additional information on Record Identifier B, refer to the Application Control chapter of this document.

**Output:** Record Identifier F411 is a mandatory location of goods (FIRMS) record. Record Identifiers F211 and F311 are conditional.

The application identifier on Record Identifier B is FR. For additional information on Record Identifier B, refer to the Application Control chapter of this document.

### **Import Specialist Team Assignment File**

The Import Specialist Team Assignment File provides the team number of the import specialist assigned to the merchandise for a specific district/port.

**Input:** Record Identifier F112 is a conditional Import Specialist Team Assignment input query record.

The application control on Record Identifier B is FI. For additional information on Record Identifier B, refer to the Application Control chapter of this document.

**Output:** Record Identifier F112 is a conditional Import Specialist Team Assignment output record.

The application control on Record Identifier B is FR. For additional information on Record Identifier B, refer to the Application Control chapter of this document.

## Record Identifier C1 (Input)

This is a mandatory antidumping/countervailing duty case query input record that allows ADD/CVD data to be queried by country and status.

| <b>Record Identifier C1 (Input)</b> |                          |                 |               |   |             |
|-------------------------------------|--------------------------|-----------------|---------------|---|-------------|
| <b>Data Element</b>                 | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>  | <b>Note</b> |
| Control Identifier                  | 1A                       | 1               | M             | Must always equal C.  |             |
| Record Type                         | 1N                       | 2               | M             | Must always equal 1.  |             |
| All Countries                       | 1X                       | 3               | C             | A code of <i>I</i> to receive case information on all countries; otherwise, space fill.   |             |
| Given Country Only                  | 2A                       | 4-5             | C             | The International Organization for Standardization (ISO) country code to receive case data for a particular country; otherwise, space fill.   |             |
| Active and Revoked                  | 1X                       | 6               | C             | A code of <i>I</i> to receive all active and revoked case data; otherwise, space fill.  |             |
| Active Records Only                 | 1X                       | 7               | C             | A code of <i>I</i> to receive all active records only; otherwise, space fill.   |             |
| Return All Information              | 1X                       | 8               | C             | A code of <i>I</i> to receive all case information (deposit rates, bond requirements, applicable tariff numbers, and manufacturer names); otherwise, space fill. If the code is <i>I</i> , Record Identifiers C2 through C8 are returned. |             |
| Return Case Information             | 1X                       | 9               | C             | A code of <i>I</i> to receive case number, related cases, case status and date, contacts bond/cash indicator and liquidation status; otherwise, space fill. If the code is <i>I</i> , Record Identifiers C2 through C4 are returned.      |             |
| Return Rates/Bonding                | 1X                       | 10              | C             | A code of <i>I</i> to receive deposit rates and bond/cash requirements; otherwise, space fill. If the code is <i>I</i> , Record Identifiers C2 and C5 are returned.   |             |
| Return Tariffs                      | 1X                       | 11              | C             | A code of <i>I</i> to receive all tariff numbers covered by the case; otherwise, space fill. If the code is <i>I</i> , Record Identifiers C2, C4 and C6 are returned.   |             |
| Return Names                        | 1X                       | 12              | C             | A code of <i>I</i> to receive all manufacturers covered by the case; otherwise, space fill. If the code is <i>I</i> , Record Identifiers C2, C7 and C8 are returned.  |             |
| Filler                              | 68X                      | 13-80           | M             | Space fill.   |             |

## Record Identifier C2 (Output)

This is a mandatory antidumping/countervailing duty case query output record that is identical to the C1 record.

| <b>Record Identifier C2 (Output)</b> |                          |                 |               |  |             |
|--------------------------------------|--------------------------|-----------------|---------------|--|-------------|
| <b>Data Element</b>                  | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>   | <b>Note</b> |
| Control Identifier                   | 1A                       | 1               | M             | Must always equal C.   |             |
| Record Type                          | 1N                       | 2               | M             | Must always equal 2.   |             |
| All Countries                        | 1X                       | 3               | C             | A code of <i>I</i> to receive case information on all countries; otherwise, space fill.  |             |
| Given Country Only                   | 2A                       | 4-5             | C             | The International Organization for Standardization (ISO) country code to receive case data for a particular country; otherwise, space fill.                      |             |
| Active and Revoked                   | 1X                       | 6               | C             | A code of <i>I</i> to receive all active and revoked case data; otherwise, space fill.   |             |
| Active Records Only                  | 1X                       | 7               | C             | A code of <i>I</i> to receive all active records only; otherwise, space fill.  |             |
| Return All Information               | 1X                       | 8               | C             | A code of <i>I</i> to receive all case information (deposit rates, bond requirements, applicable tariff numbers, and manufacturer names); otherwise, space fill. |             |
| Return Case Information              | 1X                       | 9               | C             | A code of <i>I</i> to receive case number, related cases, case status and date, contacts bond/cash indicator and liquidation status; otherwise, space fill.      |             |
| Return Rates/Bonding                 | 1X                       | 10              | C             | A code of <i>I</i> to receive deposit rates and bond/cash requirements; otherwise, space fill.   |             |
| Return Tariffs                       | 1X                       | 11              | C             | A code of <i>I</i> to receive all tariff numbers covered by the case; otherwise, space fill.   |             |
| Return Names                         | 1X                       | 12              | C             | A code of <i>I</i> to receive all manufacturers covered by the case; otherwise, space fill.  |             |
| Filler                               | 68X                      | 13-80           | M             | Space fill.  |             |

## Record Identifier C3 (Output)

This is a conditional antidumping/countervailing duty query output record that provides data pertaining to the International Organization for Standardization (ISO) country code, case number, related case number, manufacturer identification (ID) number, shipper ID, case status, case status date, and bond/cash indicator.

| <b>Record Identifier C3 (Output)</b> |                         |                 |               |  |             |                    |          |            |          |             |          |       |          |       |          |                       |          |                         |          |            |          |            |          |          |          |            |  |
|--------------------------------------|-------------------------|-----------------|---------------|--|-------------|--------------------|----------|------------|----------|-------------|----------|-------|----------|-------|----------|-----------------------|----------|-------------------------|----------|------------|----------|------------|----------|----------|----------|------------|--|
| <b>Data Element</b>                  | <b>Length/Class</b>     | <b>Position</b> | <b>Status</b> | <b>Description</b>   | <b>Note</b> |                    |          |            |          |             |          |       |          |       |          |                       |          |                         |          |            |          |            |          |          |          |            |  |
| Control Identifier                   | 1A                      | 1               | M             | Must always equal C.   |             |                    |          |            |          |             |          |       |          |       |          |                       |          |                         |          |            |          |            |          |          |          |            |  |
| Record Type                          | 1N                      | 2               | M             | Must always equal 3.   |             |                    |          |            |          |             |          |       |          |       |          |                       |          |                         |          |            |          |            |          |          |          |            |  |
| ISO Country Code                     | 2A                      | 3-4             | M             | The International Organization for Standardization (ISO) country code applicable to the antidumping/countervailing duty case. If the query is on the ISO country code, Record Identifiers C3 through C6 are returned for all cases for that country. Valid ISO codes are listed in Appendix B.   |             |                    |          |            |          |             |          |       |          |       |          |                       |          |                         |          |            |          |            |          |          |          |            |  |
| Case Number                          | 10AN                    | 5-14            | M             | A code identifying the number assigned to the antidumping/countervailing duty case.  |             |                    |          |            |          |             |          |       |          |       |          |                       |          |                         |          |            |          |            |          |          |          |            |  |
| Related Case Number                  | 10AN                    | 15-24           | C             | The number identifying any related case numbers.   |             |                    |          |            |          |             |          |       |          |       |          |                       |          |                         |          |            |          |            |          |          |          |            |  |
| Manufacturer ID Code                 | 15AN                    | 25-39           | C             | A code identifying the manufacturer.   |             |                    |          |            |          |             |          |       |          |       |          |                       |          |                         |          |            |          |            |          |          |          |            |  |
| Shipper ID                           | 15AN                    | 40-54           | C             | A code identifying the shipper.  |             |                    |          |            |          |             |          |       |          |       |          |                       |          |                         |          |            |          |            |          |          |          |            |  |
| Case Status                          | 1A                      | 55              | M             | A code representing the status of the case. Valid Case Status Codes are:<br><br><table border="0"> <thead> <tr> <th><b>Code</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td><b>I</b></td> <td>Initiation</td> </tr> <tr> <td><b>P</b></td> <td>Preliminary</td> </tr> <tr> <td><b>F</b></td> <td>Final</td> </tr> <tr> <td><b>O</b></td> <td>Order</td> </tr> <tr> <td><b>A</b></td> <td>Administrative Review</td> </tr> <tr> <td><b>S</b></td> <td>Investigation Suspended</td> </tr> <tr> <td><b>N</b></td> <td>Reinstated</td> </tr> <tr> <td><b>R</b></td> <td>Revocation</td> </tr> <tr> <td><b>E</b></td> <td>Excluded</td> </tr> <tr> <td><b>T</b></td> <td>Terminated</td> </tr> </tbody> </table> | <b>Code</b> | <b>Description</b> | <b>I</b> | Initiation | <b>P</b> | Preliminary | <b>F</b> | Final | <b>O</b> | Order | <b>A</b> | Administrative Review | <b>S</b> | Investigation Suspended | <b>N</b> | Reinstated | <b>R</b> | Revocation | <b>E</b> | Excluded | <b>T</b> | Terminated |  |
| <b>Code</b>                          | <b>Description</b>      |                 |               |  |             |                    |          |            |          |             |          |       |          |       |          |                       |          |                         |          |            |          |            |          |          |          |            |  |
| <b>I</b>                             | Initiation              |                 |               |  |             |                    |          |            |          |             |          |       |          |       |          |                       |          |                         |          |            |          |            |          |          |          |            |  |
| <b>P</b>                             | Preliminary             |                 |               |  |             |                    |          |            |          |             |          |       |          |       |          |                       |          |                         |          |            |          |            |          |          |          |            |  |
| <b>F</b>                             | Final                   |                 |               |  |             |                    |          |            |          |             |          |       |          |       |          |                       |          |                         |          |            |          |            |          |          |          |            |  |
| <b>O</b>                             | Order                   |                 |               |  |             |                    |          |            |          |             |          |       |          |       |          |                       |          |                         |          |            |          |            |          |          |          |            |  |
| <b>A</b>                             | Administrative Review   |                 |               |  |             |                    |          |            |          |             |          |       |          |       |          |                       |          |                         |          |            |          |            |          |          |          |            |  |
| <b>S</b>                             | Investigation Suspended |                 |               |  |             |                    |          |            |          |             |          |       |          |       |          |                       |          |                         |          |            |          |            |          |          |          |            |  |
| <b>N</b>                             | Reinstated              |                 |               |  |             |                    |          |            |          |             |          |       |          |       |          |                       |          |                         |          |            |          |            |          |          |          |            |  |
| <b>R</b>                             | Revocation              |                 |               |  |             |                    |          |            |          |             |          |       |          |       |          |                       |          |                         |          |            |          |            |          |          |          |            |  |
| <b>E</b>                             | Excluded                |                 |               |  |             |                    |          |            |          |             |          |       |          |       |          |                       |          |                         |          |            |          |            |          |          |          |            |  |
| <b>T</b>                             | Terminated              |                 |               |  |             |                    |          |            |          |             |          |       |          |       |          |                       |          |                         |          |            |          |            |          |          |          |            |  |
| Case Status Date                     | 6N                      | 56-61           | M             | A numeric date in MMDDYY (month, day, year) format representing the case status date.  |             |                    |          |            |          |             |          |       |          |       |          |                       |          |                         |          |            |          |            |          |          |          |            |  |

| <b>Record Identifier C3 (Output)</b> |                          |                 |               |  |             |
|--------------------------------------|--------------------------|-----------------|---------------|--|-------------|
| <b>Data Element</b>                  | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>   | <b>Note</b> |
| Bond/Cash Indicator                  | 1AN                      | 62              | M             | <p>A code indicating if a bond or cash is required. This is the latest indicator by the latest effective date returned on the C5 record. Valid Bond/Cash Indicator Codes are:</p> <p>O = Not applicable<br/>                     B = Bonded<br/>                     C = Cash required</p> |             |
| Filler                               | 18AN                     | 63-80           | M             | Space fill.  |             |

## Record Identifier C4 (Output)

This is a conditional antidumping/countervailing duty query output record that provides data pertaining to the case number, contact, phone, liquidation/suspension date, and short description.

| <b>Record Identifier C4 (Output)</b> |                          |                 |               |   |             |
|--------------------------------------|--------------------------|-----------------|---------------|---|-------------|
| <b>Data Element</b>                  | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>  | <b>Note</b> |
| Control Identifier                   | 1A                       | 1               | M             | Must always equal C.  |             |
| Record Type                          | 1N                       | 2               | M             | Must always equal 4.  |             |
| Case Number                          | 10AN                     | 3-12            | M             | A code identifying the number assigned to the antidumping/countervailing duty case.   |             |
| Contact                              | 20X                      | 13-32           | C             | The name of the contact person.   |             |
| Phone                                | 10N                      | 33-42           | C             | The phone number of the contact person (area code in positions 33-35, exchange in positions 36-38 and number in positions 39-42). |             |
| Liquidation/<br>Suspension Date      | 6N                       | 43-48           | C             | A numeric date in MMDDYY (month, day, year) format representing the liquidation/suspension date.                                  |             |
| Short Description                    | 30X                      | 49-78           | M             | A brief narrative message related to the antidumping/countervailing duty case.  |             |
| Filler                               | 2AN                      | 79-80           | M             | Space fill  |             |



## Record Identifier C5 (Output)

This is a conditional antidumping/countervailing duty query output record that provides data pertaining to the case number, rate indicator, deposit rates, and effective entry and export date, and bond/cash indicators and dates. Historical data on up to the 10 latest deposit rates will be returned. This record is repeated as often as necessary.

| <b>Record Identifier C5 (Output)</b> |                          |                 |               |  |             |
|--------------------------------------|--------------------------|-----------------|---------------|--|-------------|
| <b>Data Element</b>                  | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>   | <b>Note</b> |
| Control Identifier                   | 1A                       | 1               | M             | Must always equal C.   |             |
| Record Type                          | 1N                       | 2               | M             | Must always equal 5.   |             |
| Case Number                          | 10AN                     | 3-12            | M             | A code identifying the number assigned to the antidumping/countervailing duty case.  |             |
| Rate Indicator                       | 1N                       | 13              | M             | A code of 0 (zero) indicates no rate exists for the case; a code of 1 indicates a rate applies.  |             |
| Deposit Rate 1                       | 5N                       | 14-18           | C             | A value representing the deposit rate. Four decimal places are implied (e.g., if the deposit rate is 25%, 02500 is the rate returned).   |             |
| Deposit Rate 2                       | 5N                       | 19-23           | C             | A value representing the deposit rate. Four decimal places are implied (e.g., if the deposit rate is 25%, 02500 is the rate returned).   |             |
| Deposit Rate 3                       | 5N                       | 24-28           | C             | A value representing the deposit rate. Four decimal places are implied (e.g., if the deposit rate is 25%, 02500 is the rate returned).   |             |
| Effective Entry Date                 | 6N                       | 29-34           | C             | A numeric date in MMDDYY (month, day, year) format representing the date the deposit rate is effective for entry into the United States. |             |
| Effective Export Date                | 6N                       | 35-40           | C             | A numeric date in MMDDYY (month, day, year) format representing the date the deposit rate is effective for exported goods.               |             |
| Bond/Cash Indicator 1                | 1AN                      | 41              | M             | A code representing the first bond/cash indicator.   | 1           |
| Bond/Cash Date 1                     | 6N                       | 42-47           | M             | A numeric date in MMDDYY (month, day, year) format representing the first (earliest) bond/cash date.                                     |             |
| Bond/Cash Indicator 2                | 1AN                      | 48              | C             | A code representing the second bond/cash indicator.  | 1           |
| Bond/Cash Date 2                     | 6N                       | 49-54           | C             | A numeric date in MMDDYY (month, day, year) format representing the second bond/cash date.   |             |
| Bond/Cash Indicator 3                | 1AN                      | 55              | C             | A code representing the third bond/cash indicator.   | 1           |

| <b>Record Identifier C5 (Output)</b> |                          |                 |               |  |             |
|--------------------------------------|--------------------------|-----------------|---------------|--|-------------|
| <b>Data Element</b>                  | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>   | <b>Note</b> |
| Bond/Cash Date 3                     | 6N                       | 56-61           | C             | A numeric date in MMDDYY (month, day, year) representing the third bond/cash date.         |             |
| Bond/Cash Indicator 4                | 1N                       | 62              | C             | A code representing the fourth bond/cash indicator.  | 1           |
| Bond/Cash Date 4                     | 6N                       | 63-68           | C             | A numeric date in MMDDYY (month, day, year) format representing the fourth bond/cash date. |             |
| Bond/Cash Indicator 5                | 1AN                      | 69              | C             | A code representing the fifth bond/cash indicator.   | 1           |
| Bond/Case Date 5                     | 6N                       | 70-75           | C             | A numeric date in MMDDYY (month, day, year) format representing the fifth bond/cash date.  |             |
| Filler                               | 5X                       | 76-80           | M             | Space fill.  |             |

**Note 1**

Valid indicator codes are:

| <b>Code</b> | <b>Description</b>   |
|-------------|----------------------|
| <b>O</b>    | Not Applicable       |
| <b>B</b>    | Bonded Cash Required |
| <b>C</b>    | Cash Required        |

## Record Identifier C6 (Output)

This is a conditional antidumping/countervailing duty query output record that provides data pertaining to up to seven tariff numbers associated with the case. If the tariff number is an 8-position Harmonized Tariff Schedule (HTS) number, the case applies to all statistical suffixes for that number. This record is repeated for up to 1,000 tariff numbers.

| <b>Record Identifier C6 (Output)</b> |                          |                 |               |  |             |
|--------------------------------------|--------------------------|-----------------|---------------|--|-------------|
| <b>Data Element</b>                  | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>   | <b>Note</b> |
| Control Identifier                   | 1A                       | 1               | M             | Must always equal C.   |             |
| Record Type                          | 1N                       | 2               | M             | Must always equal 6.   |             |
| Tariff Number                        | 10X                      | 3-12            | M             | A code located in the <i>Harmonized Tariff Schedule of the United States Annotated</i> representing the tariff number. |             |
| Tariff Number                        | 10X                      | 13-22           | C             | A code located in the <i>Harmonized Tariff Schedule of the United States Annotated</i> representing the tariff number. |             |
| Tariff Number                        | 10X                      | 23-32           | C             | A code located in the <i>Harmonized Tariff Schedule of the United States Annotated</i> representing the tariff number. |             |
| Tariff Number                        | 10X                      | 33-42           | C             | A code located in the <i>Harmonized Tariff Schedule of the United States Annotated</i> representing the tariff number. |             |
| Tariff Number                        | 10X                      | 43-52           | C             | A code located in the <i>Harmonized Tariff Schedule of the United States Annotated</i> representing the tariff number. |             |
| Tariff Number                        | 10X                      | 53-62           | C             | A code located in the <i>Harmonized Tariff Schedule of the United States Annotated</i> representing the tariff number. |             |
| Tariff Number                        | 10X                      | 63-72           | C             | A code located in the <i>Harmonized Tariff Schedule of the United States Annotated</i> representing the tariff number. |             |
| Filler                               | 8AN                      | 73-80           | M             | Space fill.  |             |

## Record Identifier C7 (Output)

This is a conditional antidumping/countervailing duty query output record that provides data pertaining to the case number and manufacturer name.

| <b>Record Identifier C7 (Output)</b> |                          |                 |               |   |             |
|--------------------------------------|--------------------------|-----------------|---------------|---|-------------|
| <b>Data Element</b>                  | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>  | <b>Note</b> |
| Control Identifier                   | 1A                       | 1               | M             | Must always equal C.  |             |
| Record Type                          | 1N                       | 2               | M             | Must always equal 7.  |             |
| Case Number                          | 10AN                     | 3-12            | M             | A code identifying the number assigned to the antidumping/countervailing duty case. A case number beginning with an <i>A</i> indicates an antidumping duty case. A case number beginning with a <i>C</i> indicates a countervailing duty case number. |             |
| Manufacturer Name                    | 50X                      | 13-62           | M             | The name of the manufacturer associated with the case.  |             |
| Filler                               | 18AN                     | 63-80           | M             | Space fill.   |             |

## Record Identifier C8 (Output)

This is a conditional antidumping/countervailing duty query output record that provides data pertaining to the case number and shipper.

| <b>Record Identifier C8 (Output)</b> |                          |                 |               |   |             |
|--------------------------------------|--------------------------|-----------------|---------------|---|-------------|
| <b>Data Element</b>                  | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>  | <b>Note</b> |
| Control Identifier                   | 1A                       | 1               | M             | Must always equal C.  |             |
| Record Type                          | 1N                       | 2               | M             | Must always equal 8.  |             |
| Case Number                          | 10AN                     | 3-12            | M             | A code identifying the number assigned to the antidumping/countervailing duty case. A case number beginning with an <i>A</i> indicates an antidumping duty case. A case number beginning with a <i>C</i> indicates a countervailing duty case number. |             |
| Shipper                              | 50X                      | 13-62           | M             | The name of the shipper associated with the case.   |             |
| Filler                               | 18AN                     | 63-80           | M             | Space fill.   |             |

## Record Identifier C9 (Output)

This is a conditional antidumping/countervailing duty case query output record that provides an error message. This record is repeated as often as necessary.

| <b>Record Identifier C9 (Output)</b> |                          |                 |               |                                       |             |
|--------------------------------------|--------------------------|-----------------|---------------|---------------------------------------|-------------|
| <b>Data Element</b>                  | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>                    | <b>Note</b> |
| Control Identifier                   | 1A                       | 1               | M             | Must always equal C.                  |             |
| Record Type                          | 1N                       | 2               | M             | Must always equal 9.                  |             |
| Narrative Message                    | 30X                      | 3-32            | C             | A narrative message of the error.     |             |
| Message<br>Identification Code       | 3AN                      | 33-35           | M             | A code identifying the error message. |             |
| Filler                               | 45AN                     | 36-80           | M             | Space fill.                           |             |

## Record Identifier F101 (Input)

This is a mandatory region/district/port input record that provides data pertaining to the reference file code for the Region/District/Port Code file.

| <b>Record Identifier F101 (Input)</b> |                          |                 |               |                       |             |
|---------------------------------------|--------------------------|-----------------|---------------|-----------------------|-------------|
| <b>Data Element</b>                   | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>    | <b>Note</b> |
| Control Identifier                    | 1A                       | 1               | M             | Must always equal F.  |             |
| Record Type                           | 1N                       | 2               | M             | Must always equal 1.  |             |
| Reference File<br>Code                | 2N                       | 3-4             | M             | Must always equal 01. |             |
| Filler                                | 76AN                     | 5-80            | M             | Space fill.           |             |

## Record Identifier F101 (Output)

This is a mandatory region/district/port output record that provides data pertaining to the reference file code, region/district/port code, name, address, and carrier type.

| <b>Record Identifier F101 (Output)</b> |                          |                 |               |  |             |
|--|--------------------------|-----------------|---------------|--|-------------|
| <b>Data Element</b>                    | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>   | <b>Note</b> |
| Control Identifier                     | 1A                       | 1               | M             | Must always equal F.   |             |
| Record Type                            | 1N                       | 2               | M             | Must always equal 1.   |             |
| Reference File Code                    | 2N                       | 3-4             | M             | Must always equal 01.  |             |
| Region/District/Port Code              | 5N                       | 5-9             | M             | A code representing the region/district/port. Valid Region/District/Port Codes can be queried through Record Identifier F101 of this chapter.  |             |
| Region/District/Port Name              | 24AN                     | 10-33           | M             | The name of the region/district/port. Valid Region/District/Port Codes can be queried through Record Identifier F101 of this chapter.  |             |
| Region/District/Port Address Line 1    | 32AN                     | 34-65           | M             | The first line of the region/district/port address.  |             |
| District/Port Carrier Type             | 1AN                      | 66              | M             | <p>A code representing the district/port carrier type. Valid District/Port Carrier Type Codes are:</p> <p><b>Code Description</b></p> <p><b>B</b> All modes of transportation are valid.</p> <p><b>V</b> Vessel and other modes of transportation are valid with the exception of air.</p> <p><b>A</b> Air and other modes of transportation are valid with the exception of vessel.</p> <p><b>Space Fill</b> Air and other modes of transportation are valid with the exception of vessel (not covered by district/port carrier type code A).</p> |             |
| Primary Team Location                  | 4N                       | 67-70           | M             | The location (district/port code) where most, if not all, entry summaries are reviewed by import specialist teams. Valid district/port codes can be queried through Record Identifier F101 of this chapter.  |             |



| <b>Record Identifier F101 (Output)</b> |                          |                 |               |   |             |
|--|--------------------------|-----------------|---------------|---|-------------|
| <b>Data Element</b>                    | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>  | <b>Note</b> |
| Secondary Team Location                | 4N                       | 71-74           | C             | The location (district/port code) where some entry summaries are reviewed by teams in a location other than the primary team location. Valid district/port codes can be queried through Record Identifier F101 of this chapter. |             |
| Port of Unlading                       | 1N                       | 75              | M             | A code of <i>1</i> (valid) or <i>0</i> (invalid) indicating the validity of the port of unlading.   |             |
| Filler                                 | 5X                       | 76-80           | M             | Space fill.   |             |

## Record Identifier F201 (Output)

This is a mandatory region/district/port output record that provides data pertaining to the region/district/port code and address.

| <b>Record Identifier F201 (Output)</b> |                          |                 |               |  |             |
|--|--------------------------|-----------------|---------------|--|-------------|
| <b>Data Element</b>                    | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>   | <b>Note</b> |
| Control Identifier                     | 1A                       | 1               | M             | Must always equal F.   |             |
| Record Type                            | 1N                       | 2               | M             | Must always equal 2.   |             |
| Reference File Code                    | 2N                       | 3-4             | M             | Must always equal 01.  |             |
| Region/District/Port Code              | 5N                       | 5-9             | M             | The region/district/port code must be the same as the Region/District/Port Code in Record Identifier F101 (output).  |             |
| Region/District/Port Address Line 2    | 32AN                     | 10-41           | C             | The second line of the region/district/port address. City, state, and ZIP code are included in Record Identifier F301. If there is no second line address, space fill. |             |
| Region/District/Port Address Line 3    | 32AN                     | 42-73           | C             | The third line of the region/district/port address. City, state, and ZIP code are included in Record Identifier F301. If there is no third line address, space fill.   |             |
| Filler                                 | 7AN                      | 74-80           | M             | Space fill.  |             |

## Record Identifier F301 (Output)

This is a mandatory region/district/port output record that provides data pertaining to the region/district/port code, city, state, and ZIP code.

| <b>Record Identifier F301 (Output)</b> |                          |                 |               |   |             |
|--|--------------------------|-----------------|---------------|---|-------------|
| <b>Data Element</b>                    | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>  | <b>Note</b> |
| Control Identifier                     | 1A                       | 1               | M             | Must always equal F.  |             |
| Record Type                            | 1N                       | 2               | M             | Must always equal 3.  |             |
| Reference File Code                    | 2N                       | 3-4             | M             | Must always equal 01.   |             |
| Region/District/Port Code              | 5N                       | 5-9             | M             | The region/district/port code must be the same as the Region/District/Port Code in Record Identifier F101 (Output). |             |
| Region/District/Port City              | 15AN                     | 10-24           | M             | The city where the region/district/port is located.   |             |
| Region/District/Port State             | 2A                       | 25-26           | M             | The state where the region/district/port is located.  |             |
| Region/District/Port ZIP Code          | 9AN                      | 27-35           | M             | The ZIP code of the region/district/port.   |             |
| Filler                                 | 45AN                     | 36-80           | M             | Space fill.   |             |

## Record Identifier F401 (Output)

This is a conditional region/district/port output record that provides data pertaining to the region/district/port code and subport code.

| <b>Record Identifier F401 (Output)</b> |                          |                 |               |  |             |
|--|--------------------------|-----------------|---------------|--|-------------|
| <b>Data Element</b>                    | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>   | <b>Note</b> |
| Control Identifier                     | 1A                       | 1               | M             | Must always equal F.   |             |
| Record Type                            | 1N                       | 2               | M             | Must always equal 4.   |             |
| Reference File Code                    | 2N                       | 3-4             | M             | Must always equal 01.  |             |
| Region/District/Port Code              | 5N                       | 5-9             | M             | The Region/District/Port Code is the same as the Region/District/Port Code in Record Identifier F101 (Output).                   |             |
| Region/District/Port/Subport Code      | 5N                       | 10-14           | C             | A code representing the region/district/port subport. Valid codes can be queried through Record Identifier F101 of this chapter. |             |
| Filler                                 | 66AN                     | 15-80           | M             | Space fill.  |             |

## **Record Identifier F102 (Input)**

This is a mandatory country code input record that provides data pertaining to the reference file code for the Country Code file.

| <b><i>Record Identifier F102 (Input)</i></b> |                          |                 |               |                       |             |
|--|--------------------------|-----------------|---------------|-----------------------|-------------|
| <b>Data Element</b>                          | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>    | <b>Note</b> |
| Control Identifier                           | 1A                       | 1               | M             | Must always equal F.  |             |
| Record Type                                  | 1N                       | 2               | M             | Must always equal 1.  |             |
| Reference File Code                          | 2N                       | 3-4             | M             | Must always equal 02. |             |
| Filler                                       | 76AN                     | 5-80            | M             | Space fill.           |             |

## Record Identifier F102 (Output)

This is a mandatory country code output record that provides data pertaining to the reference file code, country, rate column indicator, restriction indicator, Generalized System of Preferences (GSP) indicator, begin and end date, special programs indicator, country name, and currency name and ISO currency code.

| <b>Record Identifier F102 (Output)</b>             |                          |                 |               |  |             |
|--|--------------------------|-----------------|---------------|--|-------------|
| <b>Data Element</b>                                | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>   | <b>Note</b> |
| Control Identifier                                 | 1A                       | 1               | M             | Must always equal F.   |             |
| Record Type  | 1N                       | 2               | M             | Must always equal 1.   |             |
| Reference File Code                                | 2N                       | 3-4             | M             | Must always equal 02.  |             |
| Country  | 2A                       | 5-6             | M             | The International Organization for Standardization (ISO) country code representing the country. Valid ISO country codes are listed in Appendix B.  |             |
| Rate Column Indicator                              | 1N                       | 7               | C             | A code indicating the column that contains the rate of duty. Valid Rate Column Indicator Codes are:<br><br>1 = Column 1<br>2 = Column 2<br>3 = Least Developed Developing Country (LDDC) |             |
| Restriction Indicator                              | 1N                       | 8               | C             | A code representing the restriction indicator. Valid Restriction Indicator Codes are:<br><br>1 = Restricted<br>0 = Not restricted  |             |
| Generalized System of Preferences (GSP) Indicator  | 1N                       | 9               | C             | A code representing the GSP indicator. Valid GSP Indicator Codes are:<br><br>0 = GSP is not applicable<br>1 = GSP is applicable  |             |
| Generalized System of Preferences (GSP) Begin Date | 6X                       | 10-15           | C             | A numeric date in MMDDYY (month, day, year) format representing the GSP begin date.  |             |
| Generalized System of Preferences (GSP) End Date   | 6X                       | 16-21           | C             | A numeric date in MMDDYY (month, day, year) format representing the GSP end date.  |             |

| <b>Record Identifier F102 (Output)</b> |                          |                 |               |   |             |
|--|--------------------------|-----------------|---------------|---|-------------|
| <b>Data Element</b>                    | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>  | <b>Note</b> |
| Special Programs Indicator (SPI) Code  | 1X                       | 22              | C             | <p>A code representing the special programs indicator. Valid Special Program Indicator Codes are:</p> <p><b>Code Description</b></p> <p><b>E</b> Caribbean Basin Initiative (CBI)<br/> <b>I</b> Israeli Free Trade Agreement<br/> <b>J</b> Andian Trade Preference Act (ATPA)<br/> <b>Y</b> Insular Possessions<br/> <b>Z</b> Freely Associated States<br/> <b>1</b> Jordon<br/> <b>2</b> Chile<br/> <b>3</b> Singapore<br/> <b>4</b> Australia<br/> <b>5</b> Morocco</p> |             |
| Country Name,                          | 30X                      | 23-52           | M             | The country name spelled out.   |             |
| Currency Name                          | 15X                      | 53-67           | C             | The currency name is reserved for future use.   |             |
| ISO Currency Code                      | 3X                       | 68-70           | C             | The currency code is reserved for future use.   |             |
| Drawback Eligibility                   | 1X                       | 71              | C             | A code of either 0 (not eligible for drawback) or 1 (eligible for drawback).  |             |
| Country Code                           | 4AN                      | 72-75           | C             | The Schedule C Country number identifying the country. Schedule C numbers are listed in Annex A of the <i>Harmonized Tariff Schedule</i> of the United States, Annotated.   |             |
| AGOA/CBTPA/ATPDEA SPI Indicator        | 1X                       | 76              | C             | <p>A code representing the eligibility to the AGOA (African Growth &amp; Opportunity Act), CBTPA (Caribbean Basin Trade Partnership Act or Andean Trade Promotion &amp; Drug Eradication Act (ATPDEA) Special Trade Programs). Valid Special Program Indicators are:</p> <p><b>Code Description</b></p> <p><b>D</b> AGOA<br/> <b>R</b> CBTPA<br/> <b>J</b> ATPDEA<br/> <b>Spaces</b> A country not considered to be an AGOA or CBTPA eligible country</p>                 |             |

| <b>Record Identifier F102 (Output)</b>                         |                          |                 |               |   |             |
|--|--------------------------|-----------------|---------------|---|-------------|
| <b>Data Element</b>  | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>  | <b>Note</b> |
| AGOA LDD Indicator (AGOA Lesser Developed Beneficiary Country) | 1X                       | 77              | C             | <p>A code indicating if the country is considered an AGOA LDD country. Valid code is:</p> <p><b>Code Description</b></p> <p><b>1</b> The country considered an AGOA LDD Country</p> <p><b>Blank</b> The country is not considered an AGOA LDD county.</p> |             |
| Filler   | 3AN                      | 78-80           | M             | Space fill.   |             |



## Record Identifier F202 (Output)

This is a conditional country code output record that provides data pertaining to a country, rate of duty, restriction, and special programs.

| <b>Record Identifier F202 (Output)</b> |                          |                 |               |  |             |
|--|--------------------------|-----------------|---------------|--|-------------|
| <b>Data Element</b>                    | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>   | <b>Note</b> |
| Control Identifier                     | 1A                       | 1               | M             | Must always equal F.   |             |
| Record Type                            | 1A                       | 2               | M             | Must always equal 2.   |             |
| Reference File Code                    | 2N                       | 3-4             | M             | Must always equal 02.  |             |
| Country                                | 2A                       | 5-6             | M             | The International Organization for Standardization (ISO) country code. Valid ISO country codes are listed in Appendix B.   |             |
| Rate Column Indicator                  | 1N                       | 7               | C             | A code indicating the column that contains the rate of duty. This field will only be shown if the Rate Column effective dates are indicated. Valid Rate Column Indicator codes are:<br><br>1 = Column 1<br>2 = Column 2<br>3 = Least Developed Developing Country (LDDC) |             |
| Rate Column Begin Date                 | 6X                       | 8-13            | C             | A numeric date in MMDDYY (month, day, year) format representing the beginning effective date for the Rate Column Indicator.  |             |
| Rate Column End Date                   | 6X                       | 14-19           | C             | A numeric date in MMDDYY (month, day, year) format representing the ending effective date for the Rate Column Indicator.   |             |
| Restriction Indicator                  | 1N                       | 20              | C             | A code representing a restriction. This field will only be shown if the restriction effective dates are indicated. Valid Restriction Indicator codes are:<br><br>0 = not restricted<br>1 = restricted  |             |
| Restriction Indicator Begin Date       | 6X                       | 21-26           | C             | A numeric date in MMDDYY (month, day, year) format representing the beginning effective date for the Restriction Indicator.  |             |
| Restriction Indicator End Date         | 6X                       | 27-32           | C             | A numeric date in MMDDYY (month, day, year) format representing the ending effective date for the Restriction Indicator.   |             |

| <b>Record Identifier F202 (Output)</b> |                          |                 |               |   |             |
|--|--------------------------|-----------------|---------------|---|-------------|
| <b>Data Element</b>                    | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>  | <b>Note</b> |
| Special Programs Indicator (SPI) Code  | 1N                       | 33              | C             | <p>A code identifying the applicable special programs. Valid Special Program Indicator codes are:</p> <p><b>Code Description</b></p> <p><b>E</b> Caribbean Basin Initiative (CBI)<br/> <b>I</b> Israeli Free Trade Agreement<br/> <b>J</b> Andian Trade Preference Act (ATPA)<br/> <b>Y</b> Insular Possessions<br/> <b>Z</b> Freely Associated States<br/> <b>1</b> Jordon<br/> <b>2</b> Chile<br/> <b>3</b> Singapore<br/> <b>4</b> Australia<br/> <b>5</b> Morocco</p> |             |
| Special Programs Indicator Begin Date  | 6X                       | 34-39           | C             | A numeric date in MMDDYY (month, day, year) format representing the beginning effective date for the Special Programs Indicator.  |             |
| Special Programs Indicator End Date    | 6X                       | 40-45           | C             | A numeric date in MMDDYY (month, day, year) format representing the ending date for the Special Programs Indicator.   |             |
| AGOA/CBTPA/ATPDEA SPI Indicator        | 1X                       | 46              | C             | <p>A code representing the eligibility to the AGOA (African Growth &amp; Opportunity Act), CBTPA (Caribbean Basin Trade Partnership Act or Andean Trade Promotion &amp; Drug Eradication Act (ATPDEA) Special Trade Programs). Valid Special Program Indicators are:</p> <p><b>Code Description</b></p> <p><b>D</b> AGOA<br/> <b>R</b> CBTPA<br/> <b>J</b> ATPDEA<br/> <b>Spaces</b> A country not considered to be an AGOA or CBTPA eligible country.</p>                |             |

| <b>Record Identifier F202 (Output)</b>                         |                          |                 |               |  |             |
|--|--------------------------|-----------------|---------------|--|-------------|
| <b>Data Element</b>  | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>   | <b>Note</b> |
| AGOA LDD Indicator (AGOA Lesser Developed Beneficiary Country) | 1X                       | 47              | C             | <p>A code indicating if the country is considered an AGOA LDD country. Valid code is:</p> <p><b>Code Description</b></p> <p><b>1</b> The country considered an AGOA LDD Country</p> <p><b>Blank</b> The country is not considered an AGOA LDD county.</p>  |             |
| AGOA/CBTPA/ ATPDEA Special Programs Indicator Begin Date       | 6X                       | 48-53           | C             | <p>A date in MMDDYY (month, day, year) format representing the beginning date for the AGOA/CBTPA/ATPDEA Special Programs Indicator. If the AGOA/CBTPA/ATPDEA indicator = D in position 46, then positions 48-53 represents the begin date for the AGOA trade program. If the AGOA/CBTPA/ ATPDEA = R, in position 46, then positions 48-53 represents the begin date for the CBTPA trade program. If the AGOA/CBTPA/ ATPDEA indicator = J in position 46, then positions 48-53 represents the begin date for the ATPDEA trade program.</p>  |             |
| AGOA/CBTPA/ ATPDEA Special Programs Indicator End Date         | 6X                       | 54-59           | C             | <p>A date in MMDDYY (month, day, year) format representing the ending date for the AGOA/CBTPA/ATPDEA Special Programs Indicator. If the AGOA/CBTPA/ATPDEA indicator = D in position 46, then positions 54-59 represents the end date of the AGOA trade program. If the AGOA/CBTPA/ATPDEA indicator = "R", in position 46, then positions 54-59 represents the end date of the CBTPA trade program. If the AGOA/CBTPA/ ATPDEA indicator = J, in position 46, then positions 54-59 represents the end date for the ATPDEA trade program.</p> |             |
| Miscellaneous SPI Indicator                                    | 2X                       | 60-61           | C             | <p>A code of "P" indicates eligible for CAFTA benefits. Even though the CAFTA SPI indicator is one byte in length, this field was made two bytes in length for future trade agreements.</p>  |             |

| <b>Record Identifier F202 (Output)</b> |                          |                 |               |  |             |
|--|--------------------------|-----------------|---------------|--|-------------|
| <b>Data Element</b>                    | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>   | <b>Note</b> |
| Miscellaneous SPI<br>Begin Date        | 6X                       | 62-67           | C             | A numeric date in MMDDYY (month, day, year) format, representing the begin date for the miscellaneous indicator. If the miscellaneous indicator is "P", indicates the begin date for CAFTA benefits. |             |
| Miscellaneous SPI<br>End Date          | 6X                       | 68-73           | C             | A numeric date in MMDDYY (month, day, year) format, representing the end date for the miscellaneous indicator. If the miscellaneous indicator is "P", indicates the end date for the CAFTA benefits. |             |
| Filler                                 | 7AN                      | 74-80           | M             | Space fill.  |             |

## **Record Identifier F104 (Input)**

This is a mandatory port code (Schedule K) input record that provides data pertaining to the reference file code for the Foreign Port Code file.

| <b><i>Record Identifier F104 (Input)</i></b> |                          |                 |               |                       |             |
|--|--------------------------|-----------------|---------------|-----------------------|-------------|
| <b>Data Element</b>                          | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>    | <b>Note</b> |
| Control Identifier                           | 1A                       | 1               | M             | Must always equal F.  |             |
| Record Type                                  | 1N                       | 2               | M             | Must always equal 1.  |             |
| Reference File Code                          | 2N                       | 3-4             | M             | Must always equal 04. |             |
| Filler                                       | 76AN                     | 5-80            | M             | Space fill.           |             |

## Record Identifier F104 (Output)

This is a mandatory foreign port of lading code (Schedule K) output record that provides data pertaining to the reference file code, foreign port of lading code, and foreign port of lading name.

| <b>Record Identifier F104 (Output)</b> |                          |                 |               |   |             |
|--|--------------------------|-----------------|---------------|---|-------------|
| <b>Data Element</b>                    | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>                                  | <b>Note</b> |
| Control Identifier                     | 1A                       | 1               | M             | Must always equal F.                                |             |
| Record Type                            | 1N                       | 2               | M             | Must always equal 1.,                               |             |
| Reference File Code                    | 2N                       | 3-4             | M             | Must always equal 04.                               |             |
| Foreign Port of Lading Code            | 5N                       | 5-9             | M             | The code identifying the foreign port of lading.    |             |
| Foreign Port of Lading Name            | 30A                      | 10-39           | C             | The name of the foreign port of lading spelled out. |             |
| Filler                                 | 41AN                     | 40-80           | M             | Space fill.   |             |

## **Record Identifier F105 (Input)**

This is a mandatory ZIP and state code input record that provides data pertaining to the reference file code for the ZIP Code and State code file.

| <b><i>Record Identifier F105 (Input)</i></b> |                          |                 |               |                       |             |
|--|--------------------------|-----------------|---------------|-----------------------|-------------|
| <b>Data Element</b>                          | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>    | <b>Note</b> |
| Control Identifier                           | 1A                       | 1               | M             | Must always equal F.  |             |
| Record Type                                  | 1N                       | 2               | M             | Must always equal 1.  |             |
| Reference File Code                          | 2N                       | 3-4             | M             | Must always equal 05. |             |
| Filler                                       | 76AN                     | 5-80            | M             | Space fill.           |             |

## Record Identifier F105 (Output)

This is a mandatory ZIP code and state code output record that provides data pertaining to the reference file code, ZIP code range, and state code.

| <b>Record Identifier F105 (Output)</b> |                          |                 |               |   |             |
|--|--------------------------|-----------------|---------------|---|-------------|
| <b>Data Element</b>                    | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>  | <b>Note</b> |
| Control Identifier                     | 1A                       | 1               | M             | Must always equal F.                                      |             |
| Record Type                            | 1N                       | 2               | M             | Must always equal 1.                                      |             |
| Reference File Code                    | 2N                       | 3-4             | M             | Must always equal 05.                                     |             |
| Begin ZIP Code Range                   | 3X                       | 5-7             | C             | The ZIP code range associated with the low value.         |             |
| End ZIP Code Range                     | 3X                       | 8-10            | C             | The ZIP code range associated with the high value.        |             |
| State                                  | 2A                       | 11-12           | M             | The United States Postal Service state abbreviation code. |             |
| Filler                                 | 68AN                     | 13-80           | M             | Space fill.   |             |



## **Record Identifier F106 (Input)**

This is a mandatory carrier input record that provides data pertaining to the reference file code for the Carrier Code file. To receive only air carrier data, complete all data elements except the vessel carrier name and carrier code. Record Identifier F106 (output) will generate a complete list of all air carrier names and codes, and air waybill prefixes.

| <b>Record Identifier F106 (Input)</b> |                          |                 |               |   |             |
|---------------------------------------|--------------------------|-----------------|---------------|---|-------------|
| <b>Data Element</b>                   | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>                                  | <b>Note</b> |
| Control Identifier                    | 1A                       | 1               | M             | Must always equal F.                                |             |
| Record Type                           | 1N                       | 2               | M             | Must always equal 1.                                |             |
| Reference File Code                   | 2N                       | 3-4             | M             | Must always equal 06.                               |             |
| Carrier Name                          | 35AN                     | 5-39            | C             | The carrier name spelled out.                       |             |
| Carrier Code                          | 4AN                      | 40-43           | C             | A 2, 3, or 4 position code identifying the carrier. |             |
| Filler                                | 37AN                     | 44-80           | M             | Space fill.   |             |

## Record Identifier F106 (Output)

This is a mandatory carrier output record that provides data pertaining to the reference file code, carrier name, code and mode of transportation codes. The file contains a complete list of all air carrier modes of transportation, address and air waybill prefix. Addresses are not maintained for air carriers and some vessel carriers. When the vessel carrier name is provided on Record Identifier F106 (input), ACS will match the characters provided. Only the first exact match will be included in this output record. If there is no match, an error message is system generated.

| <b>Record Identifier F106 (Output)</b> |                          |                 |               |  |             |
|--|--------------------------|-----------------|---------------|--|-------------|
| <b>Data Element</b>                    | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>   | <b>Note</b> |
| Control Identifier                     | 1A                       | 1               | M             | Must always equal F.   |             |
| Record Type                            | 1N                       | 2               | M             | Must always equal 1.   |             |
| Reference File Code                    | 2N                       | 3-4             | M             | Must always equal 06.  |             |
| Carrier Code                           | 4AN                      | 5-8             | M             | A 2, 3, or 4 position code identifying the carrier.  |             |
| Carrier Name                           | 35X                      | 9-43            | M             | The carrier name spelled out.  |             |
| Carrier Mode of Transportation         | 2N                       | 44-45           | C             | A code representing the carrier mode of transportation. Only Air Carrier Codes will be provided. | 1           |
| Carrier Address                        | 32X                      | 46-77           | C             | The address of the carrier.  |             |
| Airway Bill Prefix                     | 3AN                      | 78-80           | C             | The International Air Transport Association (IATA) prefix.                                       |             |

### Note 1

Valid Carrier Mode of Transportation Codes are:

| <b>Code</b> | <b>Description</b>   |
|-------------|--|
| 10          | Vessel, non-container or unable to determine if container (e.g., Lightered, Land Bridge, and LASH) |
| 11          | Vessel, container  |
| 12          | Border, water-borne  |
| 20          | Rail   |
| 30          | Truck  |
| 32          | Auto   |
| 33          | Pedestrian   |
| 34          | Road (e.g., foot and animal-borne)   |
| 40          | Air  |
| 41          | Air Container  |
| 50          | Mail   |

### Note 1 - Continued

| <b>Code</b> | <b>Description</b> |
|-------------|--------------------|
|-------------|--------------------|

- 60** Passenger, hand-carried
- 70** Fixed transport (e.g., pipeline & powerhouse)
- 80** Not used at this time

## Record Identifier F107 (Input)

This is a mandatory gold price input record that provides data pertaining to the reference file code for the Gold Price file.

| <b>Record Identifier F107 (Input)</b> |                          |                 |               |   |             |
|---------------------------------------|--------------------------|-----------------|---------------|---|-------------|
| <b>Data Element</b>                   | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>  | <b>Note</b> |
| Control Identifier                    | 1A                       | 1               | M             | Must always equal F.  |             |
| Record Type                           | 1N                       | 2               | M             | Must always equal 1.  |             |
| Reference File Code                   | 2N                       | 3-4             | M             | Must always equal 07.   |             |
| Gold Price Date                       | 6N                       | 5-10            | M             | A numeric date in MMDDYY (month, day, year) format representing the date the gold price is effective. |             |
| Filler                                | 70AN                     | 11-80           | M             | Space fill.   |             |

## Record Identifier F107 (Output)

This is a mandatory gold price output record that provides data pertaining to the reference file code, gold price date, gold price, and narrative message.

| <b>Record Identifier F107 (Output)</b> |                     |                 |               |  |             |
|--|---------------------|-----------------|---------------|--|-------------|
| <b>Data Element</b>                    | <b>Length/Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>   | <b>Note</b> |
| Control Identifier                     | 1A                  | 1               | M             | Must always equal F.   |             |
| Record Identifier                      | 1N                  | 2               | M             | Must always equal 1.   |             |
| Reference File Code                    | 2N                  | 3-4             | M             | Must always equal 07.  |             |
| Gold Price Date                        | 6N                  | 5-10            | M             | A numeric date in MMDDYY (month, day, year) format representing the gold price date.   |             |
| Gold Price                             | 10N                 | 11-20           | M             | A value representing the gold price. Two decimal places are implied. If the gold price is a whole number, the two low-order (cents) positions contain zeros. |             |
| Narrative Message                      | 30X                 | 21-50           | C             | A narrative message pertaining to the gold price.  | 1           |
| Filler                                 | 30AN                | 51-80           | M             | Space fill.  |             |

### Note 1

A narrative message is system generated under the following conditions:

- If no record exists for the date queried, the gold price is zero and the narrative message is NO RECORD FOR THIS DATE.
- If a record is found for the date queried, but the market was closed on that date, the gold price is zero and the narrative message is MARKET WAS CLOSED THIS DATE.

It is understood that the gold price information is provided as an advisory tool for use by the trade. While CBP has extended significant quality control efforts in maintaining this data, CBP does not guarantee its accuracy or completeness.

## Record Identifier F108 (Input)

This is a mandatory currency query input record that provides data pertaining to the reference file code, International Organization for Standardization (ISO) country code, ISO currency code, and the beginning and ending exchange rate dates.

| <b>Record Identifier F108 (Input)</b> |                          |                 |               |  |             |
|---------------------------------------|--------------------------|-----------------|---------------|--|-------------|
| <b>Data Element</b>                   | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>   | <b>Note</b> |
| Control Identifier                    | 1A                       | 1               | M             | Must always equal F.   |             |
| Record Type                           | 1N                       | 2               | M             | Must always equal 1.   |             |
| Reference File Code                   | 2N                       | 3-4             | M             | Must always equal 08.  |             |
| ISO Country Code                      | 2A                       | 5-6             | O             | The International Organization for Standardization (ISO) country code identifying the country associated with the currency code. Valid ISO country codes are listed in Appendix B. |             |
| Filler                                | 1AN                      | 7               | M             | Space fill.  |             |
| ISO Currency Code                     | 3A                       | 8-10            | C             | The ISO currency code identifying the type of currency. Valid ISO currency codes are listed in Appendix B.   |             |
| Filler                                | 1AN                      | 11              | M             | Space fill.  |             |
| Exchange Rate Date (Beginning)        | 6N                       | 12-17           | O             | A numeric date in MMDDYY (month, day, year) format representing the date the exchange rate became effective.   |             |
| Exchange Rate Date (Ending)           | 6N                       | 18-23           | O             | A numeric date in MMDDYY (month, day, year) format representing the date the exchange rate ceased to exist.  |             |
| Filler                                | 57AN                     | 24-80           | M             | Space fill.  |             |

## Record Identifier F108 (Output)

A mandatory currency query output record that provides data pertaining to the reference file code, query results code, International Organization for Standardization (ISO) country code, ISO currency code, exchange rate and indicator.

| <b>Record Identifier F108 (Output)</b> |                          |                 |               |   |             |
|--|--------------------------|-----------------|---------------|---|-------------|
| <b>Data Element</b>                    | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>  | <b>Note</b> |
| Control Identifier                     | 1A                       | 1               | M             | Must always equal F.  |             |
| Record Type                            | 1N                       | 2               | M             | Must always equal 1.  |             |
| Reference File Code                    | 2N                       | 3-4             | M             | Must always equal 08.   |             |
| Filler                                 | 1AN                      | 5               | M             | Space fill.   |             |
| Query Results Code                     | 1N                       | 6               | M             | A code representing the query results. Valid Query Results Codes are:<br><br>0 = Currency rate on file<br>1 = No currency rate on file  |             |
| Edit Results Code                      | 1N                       | 7               | M             | A code representing the edit results. Valid Edit Results Codes are:<br><br>0 = Edits passed<br>1 = Country invalid<br>2 = Currency invalid<br>3 = Date 1 invalid<br>4 = Date 2 invalid<br>5 = Date 1 is greater than date 2 |             |
| Filler                                 | 1AN                      | 8               | M             | Space fill.   |             |
| ISO Country Codes                      | 2A                       | 9-10            | M             | The International Organization for Standardization (ISO) country code for the country associated with the currency code. Valid ISO country codes are listed in Appendix B.  |             |
| ISO Currency Code                      | 3A                       | 11-13           | M             | The ISO currency code identifying the type of currency. Valid ISO currency codes are listed in Appendix B.  |             |
| Exchange Rate Date                     | 6N                       | 14-19           | M             | A numeric date in MMDDYY (month, day, year) format representing the date the exchange rate is effective.  |             |
| Exchange Rate                          | 7N                       | 20-26           | M             | The currency rate of exchange. Six decimal places are implied. If the rate returned is 0123456, the exchange rate is 0.123456.  |             |

| <b>Record Identifier F108 (Output)</b> |                          |                 |               |  |             |
|--|--------------------------|-----------------|---------------|--|-------------|
| <b>Data Element</b>                    | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>   | <b>Note</b> |
| Indicator 1                            | 1A                       | 27              | M             | <p>A code indicating the type of exchange rate. Valid Indicator Codes are:</p> <p><b>Code Description</b></p> <p><b>Q</b> Quarterly<br/> <b>D</b> Daily<br/> <b>N</b> None (Not available from the Federal Reserve Bank for that date)<br/> <b>X</b> Reserved for future use</p> <p>If the rate for a given date is not available, the indicator returned is <i>N</i> and the rate is <i>0000000</i>. A record with an indicator of <i>N</i> is valid.</p> |             |
| Remarks                                | 50X                      | 28-77           | C             | A narrative explanation of the exchange rates.   |             |
| Filler                                 | 3AN                      | 78-80           | M             | Space fill.  |             |



## Record Identifier F208 (Output)

A conditional currency query output record that provides data pertaining to reference file code, International Organization for Standardization (ISO) country code, exchange rate date, exchange rates 2 and 3, and indicators 2 and 3.

| <b>Record Identifier F208 (Output)</b> |                          |                 |               |   |             |
|--|--------------------------|-----------------|---------------|---|-------------|
| <b>Data Element</b>                    | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>  | <b>Note</b> |
| Control Identifier                     | 1A                       | 1               | M             | Must always equal F.  |             |
| Record Type                            | 1N                       | 2               | M             | Must always equal 2.  |             |
| Reference File Code                    | 2N                       | 3-4             | M             | Must always equal 08.   |             |
| Filler                                 | 4AN                      | 5-8             | M             | Space fill.   |             |
| ISO Country Code                       | 2A                       | 9-10            | M             | An International Organization for Standardization (ISO) country code representing the country for the currency.                       |             |
| Filler                                 | 3AN                      | 11-13           | M             | Space fill.   |             |
| Exchange Rate Date                     | 6N                       | 14-19           | M             | A numeric date in MMDDYY (month, day, year) format representing the exchange rate date.   |             |
| Exchange Rate 2                        | 7N                       | 20-26           | M             | The second currency rate of exchange. Six decimal places are implied. If the rate returned is 0123456, the exchange rate is 0.123456. |             |
| Indicator 2                            | 1A                       | 27              | M             | A code indicating the type of exchange rate.  | 1           |
| Filler                                 | 1AN                      | 28              | M             | Space fill.   |             |
| Exchange Rate 3                        | 7N                       | 29-35           | C             | The third currency rate of exchange. Six decimal places are implied. If the rate returned is 0123456, the exchange rate is 0.123456.  |             |
| Indicator 3                            | 1A                       | 36              | C             | A code indicating the type of exchange rate.  | 1           |
| Filler                                 | 44AN                     | 37-80           | M             | Space fill.   |             |

### Note 1

Valid Indicator Codes are:

| <b>Code</b> | <b>Description</b>   |
|-------------|--|
| <b>Q</b>    | Quarterly  |
| <b>D</b>    | Daily  |
| <b>N</b>    | None (Not available from the Federal Reserve Bank for that date) |
| <b>X</b>    | Reserved for future use  |

If the rate for a given date is not available, the indicator returned is *N* and the rate is *0000000*. A record with an indicator of *N* is valid.

## Record Identifier F109 (Input)

This is a mandatory currency conversion query input record that provides data pertaining to the reference file code, International Organization for Standardization (ISO) country code, ISO currency code, exchange rate date and foreign currency amount. If the user supplies the country, currency, currency amount, and date for which the conversion is desired, the Automated Commercial System (ACS) will return the calculated dollar amount. If there are remarks on the file associated with the query or the query request contained errors, Record Identifier F209 is system generated.

| <b>Record Identifier F109 (Input)</b> |                          |                 |               |   |             |
|---------------------------------------|--------------------------|-----------------|---------------|---|-------------|
| <b>Data Element</b>                   | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>  | <b>Note</b> |
| Control Identifier                    | 1A                       | 1               | M             | Must always equal F.  |             |
| Record Type                           | 1N                       | 2               | M             | Must always equal 1.  |             |
| Reference File Code                   | 2N                       | 3-4             | M             | Must always equal 09.   |             |
| ISO Country Code                      | 2A                       | 5-6             | M             | The International Organization for Standardization (ISO) country code for the currency. Valid ISO country codes are listed in Appendix B. |             |
| ISO Currency Code                     | 3A                       | 7-9             | M             | The ISO currency code. Valid ISO currency codes are listed in Appendix B.   |             |
| Exchange Rate Date                    | 6N                       | 10-15           | M             | A numeric date in MMDDYY (month, day, year) format representing the currency exchange rate date.  |             |
| Filler                                | 1AN                      | 16              | M             | Space fill.   |             |
| Foreign Currency Amount               | 12N                      | 17-28           | M             | The amount of the foreign currency. Two decimal places are implied.   |             |
| Filler                                | 52AN                     | 29-80           | M             | Space fill.   |             |

## Record Identifier F109 (Output)

This is a mandatory currency conversion query output record that provides data pertaining to the reference file code, International Organization for Standardization (ISO) country code, ISO currency code, exchange rate date, query results code and up to three exchange rates, indicators, and equivalent dollar amounts.

| <b>Record Identifier F109 (Output)</b> |                     |                 |               |   |             |
|--|---------------------|-----------------|---------------|---|-------------|
| <b>Data Element</b>                    | <b>Length/Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>  | <b>Note</b> |
| Control Identifier                     | 1A                  | 1               | M             | Must always equal F.  |             |
| Record Type                            | 1N                  | 2               | M             | Must always equal 1.  |             |
| Reference File Code                    | 2N                  | 3-4             | M             | Must always equal 09.   |             |
| ISO Country Code                       | 2A                  | 5-6             | M             | The International Organization for Standardization (ISO) country code associated with the currency. Valid ISO country codes are listed in Appendix B. |             |
| ISO Currency Code                      | 3A                  | 7-9             | M             | The ISO code identifying the currency. Valid ISO currency codes are listed in Appendix B.   |             |
| Exchange Rate Date                     | 6N                  | 10-15           | M             | A numeric date in MMDDYY (month, day, year) format representing the exchange rate date.   |             |
| Query Results Code                     | 1N                  | 16              | M             | A code representing the query results. Valid Query Results Codes are:<br><br>0 = Rate found<br>1 = No rate found                                      |             |
| Filler                                 | 1AN                 | 17              | M             | Space fill.   |             |
| Exchange Rate                          | 7N                  | 18-24           | C             | The currency rate of exchange. Six decimal places are implied. If the rate returned is 0123456, the exchange rate is 0.123456.                        |             |
| Indicator 1                            | 1A                  | 25              | C             | A code indicating the type of exchange rate.  | 1           |
| Equivalent Dollar Amount 1             | 12N                 | 26-37           | C             | The equivalent amount in U.S. dollars. Two decimal places are implied.  |             |
| Filler                                 | 1AN                 | 38              | M             | Space fill.   |             |
| Exchange Rate 2                        | 7N                  | 39-45           | C             | The second currency rate of exchange. Six decimal places are implied. If the rate returned is 0123456, the exchange rate is 0.123456.                 |             |
| Indicator 2                            | 1A                  | 46              | C             | A code indicating the second exchange rate type.  | 1           |
| Equivalent Dollar Amount 2             | 12N                 | 47-58           | C             | The equivalent amount in U.S. dollars associated with the second exchange rate. Two decimal places are implied.                                       |             |
| <b>Record Identifier F109 (Output)</b> |                     |                 |               |   |             |
| <b>Data Element</b>                    | <b>Length/Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>  | <b>Note</b> |

*Customs and Trade Automated Interface Requirements*

|                            |     |       |   |  |   |
|----------------------------|-----|-------|---|--|---|
| Filler                     | 1AN | 59    | M | Space fill.  |   |
| Exchange Rate 3            | 7N  | 60-66 | C | The third currency rate of exchange. Six decimal places are implied. If the rate returned is 0123456, the exchange rate is 0.123456. |   |
| Indicator 3                | 1A  | 67    | C | A code indicating the third exchange rate type.  | 1 |
| Equivalent Dollar Amount 3 | 12N | 68-79 | C | The equivalent amount in U.S. dollars associated with the third rate of exchange. Two decimal places are implied.                    |   |
| Filler                     | 1AN | 80    | M | Space fill.  |   |

**Note 1**

Valid Indicator Codes are:

| <b>Code</b> | <b>Description</b>   |
|-------------|--|
| <b>Q</b>    | Quarterly  |
| <b>D</b>    | Daily  |
| <b>N</b>    | None (Not available from the Federal Reserve Bank for that date) |
| <b>X</b>    | Reserved for future use  |

If the rate for a given date is not available, the indicator returned is *N* and the rate is *0000000*. A record with an indicator of *N* is valid.

## Record Identifier F209 (Output)

A conditional currency conversion query output record that provides data pertaining to the reference file code, International Organization for Standardization (ISO) country code, exchange rate date, remarks, and a narrative message. Results are received only for the date used on input.

| <b>Record Identifier F209 (Output)</b> |                          |                 |               |  |             |
|--|--------------------------|-----------------|---------------|--|-------------|
| <b>Data Element</b>                    | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>   | <b>Note</b> |
| Control Identifier                     | 1A                       | 1               | M             | Must always equal F.   |             |
| Record Type                            | 1N                       | 2               | M             | Must always equal 2.   |             |
| Reference File Code                    | 2N                       | 3-4             | M             | Must always equal 09.  |             |
| ISO Country Code                       | 2A                       | 5-6             | M             | The International Organization for Standardization (ISO) country code for the country associated with the currency code. Valid ISO country codes are listed in Appendix B.       |             |
| Exchange Rate Date                     | 6N                       | 7-12            | M             | A numeric date in MMDDYY (month, day, year) format representing the currency exchange rate date.   |             |
| Remarks                                | 50X                      | 13-62           | C             | A narrative message.   |             |
| Narrative                              | 18X                      | 63-80           | C             | The narrative messages are:<br><br>NO RATE THIS DATE<br>NOT AVAILABLE<br>INVALID AMOUNT<br>INVALID DATE<br>INVALID COUNTRY<br>INVALID CURRENCY CODE<br>INVALID ISO CURRENCY CODE |             |

## Record Identifier F110 (Input)

A mandatory input record that requests update data for a range of Harmonized Tariff Schedule (HTS) tariff numbers. ACS users will be advised by an administrative message when updates are available.

| <b>Record Identifier F110 (Input)</b> |                          |                 |               |   |             |
|---------------------------------------|--------------------------|-----------------|---------------|---|-------------|
| <b>Data Element</b>                   | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>  | <b>Note</b> |
| Control Identifier                    | 1A                       | 1               | M             | Must always equal F.  |             |
| Record Type Code                      | 1N                       | 2               | M             | Must always equal 1.  |             |
| Reference File Code                   | 2N                       | 3-4             | M             | Must always equal 10.   |             |
| Harmonized Update Number              | 4N                       | 5-8             | O             | A number representing the HTS update number. Each succeeding update during the year will be incremented by one. If this data element is space filled, the latest (highest) update numbers are transmitted.  |             |
| From Harmonized Number                | 10AN                     | 9-18            | O             | A number representing the starting point for the HTS update. Update records are transmitted beginning with the first record that is equal to or greater than this number. If this data element is space filled, updates beginning with the lowest number are transmitted.                             |             |
| To Harmonized Number                  | 10AN                     | 19-28           | O             | The last HTS number included in the update will be the first record that is greater than this number. Records equal to this number are included. If this data element is space filled, updates equal to or greater than the From Harmonized Number are to be extracted to the end of the update file. |             |
| Filler                                | 52AN                     | 29-80           | M             | Space fill.   |             |

## Record Identifier F110 (Output)

This is a mandatory output extract reference file record that provides Harmonized Tariff Schedule (HTS) data for a range of tariff numbers and a narrative message.

| <b>Record Identifier F110 (Output)</b> |                          |                 |               |   |             |
|--|--------------------------|-----------------|---------------|---|-------------|
| <b>Data Element</b>                    | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>  | <b>Note</b> |
| Control Identifier                     | 1A                       | 1               | M             | Must always equal F.  |             |
| Record Identifier                      | 1N                       | 2               | M             | Must always equal 1.  |             |
| Reference File Code                    | 2N                       | 3-4             | M             | Must always equal 10.   |             |
| Harmonized Update Number               | 4N                       | 5-8             | O             | The Harmonized Update Number from Record Identifier F110 (Input). If no Harmonized Update Number was provided in Record Identifier F110 (Input), updates from the first update number are provided.                                       |             |
| From Harmonized Number                 | 10AN                     | 9-18            | O             | The From Harmonized Number from Record Identifier F110 (Input).   |             |
| To Harmonized Number                   | 10AN                     | 19-28           | O             | The To Harmonized Number from Record Identifier F110 (Input)  |             |
| Narrative Message                      | 52AN                     | 29-80           | O             | A narrative message explaining the processing results. Messages are:<br><br>INVALID UPDATE NUMBER TARIFF RANGE INCORRECTLY SPECIFIED<br>NO UPDATES FOUND IN THIS RANGE<br><br>If there are no errors, the updated records are transmitted |             |

## Record Identifier F111 (Input)

The is a mandatory location of goods (FIRMS) input record that provides data pertaining to the reference file code, FIRMS code, name of facility, district code, and begin date. The FIRMS code is located on Record Identifiers 20 (Entry Summary, X10 (Line Release), and H2 (Cargo Release). All records associated with the query are returned. For example, if the facility name query is *YEL*, data for all facility names beginning with *YEL* are returned. Likewise, if the facility name query is *Y*, data for all facility names beginning with *Y* are returned.

| <b>Record Identifier F111 (Input)</b> |                          |                 |               |  |             |
|---------------------------------------|--------------------------|-----------------|---------------|--|-------------|
| <b>Data Element</b>                   | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>   | <b>Note</b> |
| Control Identifier                    | 1A                       | 1               | M             | Must always equal F.   |             |
| Record Type                           | 1N                       | 2               | M             | Must always equal 1.   |             |
| Reference File Code                   | 2N                       | 3-4             | M             | Must always equal 11.  |             |
| FIRMS Code                            | 4N                       | 5-8             | C             | A Facilities Information and Resources Management System (FIRMS) code representing the location of goods. Each FIRMS Code query transaction requires the transmission of only one F111 record. Any number of F111 records can be included in a single transmission, batch or block. If this record contains a FIRMS Code, the Name of the Facility (positions 9-43) and the District Code (positions 44-45) must be space filled.  |             |
| Name of Facility                      | 35X                      | 9-43            | C             | The name of the facility where the goods are located. This name is left justified. If there is a FIRMS Code in positions 5-8, space fill. If there is a Facility Name, the District Code (positioned 44-45) is required. No matter how many characters are transmitted in the Name of Facility field, data is returned for all FIRMS codes assigned to the specific district which have the same set of characters at the beginning of the facility name in the FIRMS Code file. For example, if <i>Yellow</i> is transmitted in the Name of Facility field, data for all records associated with the specified district and having the facility name beginning with <i>Yellow</i> are returned. |             |



| <b>Record Identifier F111 (Input)</b> |                          |                 |               |   |             |
|---------------------------------------|--------------------------|-----------------|---------------|---|-------------|
| <b>Data Element</b>                   | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>  | <b>Note</b> |
| District Code                         | 2N                       | 44-45           | C             | The district code is the first two numbers of the district/port code. Valid District/Port Codes can be queried through Record Identifier F101 of this chapter. If there is a FIRMS Code in positions 5-8, space fill. A query can be on the District Code or on the District Code and Name of Facility.   |             |
| Begin Date                            | 6N                       | 46-51           | C             | A numeric date in MMDDYY (month, day, year) format representing the begin date. This date cannot be in the future. If a begin date is used, only those FIRMS codes which were added or updated on or after that date will be returned. A query by begin date can only be requested if the begin date is transmitted by itself or in conjunction with a district code. The FIRMS code or facility name cannot be used with a begin date. |             |
| Filler                                | 29AN                     | 52-80           | M             | Space fill.   |             |

## Record Identifier F211 (Output)

This is a conditional location of goods (FIRMS) output record that provides data pertaining to the reference file code, district/port code, FIRMS code, status, facility type and name of the facility.

| <b>Record Identifier F211 (Output)</b> |                           |                 |               |  |             |                    |           |                           |           |                    |           |      |           |                  |           |                     |           |                     |           |                      |           |                         |  |
|--|---------------------------|-----------------|---------------|--|-------------|--------------------|-----------|---------------------------|-----------|--------------------|-----------|------|-----------|------------------|-----------|---------------------|-----------|---------------------|-----------|----------------------|-----------|-------------------------|--|
| <b>Data Element</b>                    | <b>Length/<br/>Class</b>  | <b>Position</b> | <b>Status</b> | <b>Description</b>   | <b>Note</b> |                    |           |                           |           |                    |           |      |           |                  |           |                     |           |                     |           |                      |           |                         |  |
| Control Identifier                     | 1A                        | 1               | M             | Must always equal F.   |             |                    |           |                           |           |                    |           |      |           |                  |           |                     |           |                     |           |                      |           |                         |  |
| Record Type                            | 1N                        | 2               | M             | Must always equal 2.   |             |                    |           |                           |           |                    |           |      |           |                  |           |                     |           |                     |           |                      |           |                         |  |
| Reference File Code                    | 2N                        | 3-4             | M             | Must always equal 11.  |             |                    |           |                           |           |                    |           |      |           |                  |           |                     |           |                     |           |                      |           |                         |  |
| District/Port Code                     | 4N                        | 5-8             | M             | A code representing the district/port code. Valid district/port codes can be queried through Record Identifier F101 of this chapter.   |             |                    |           |                           |           |                    |           |      |           |                  |           |                     |           |                     |           |                      |           |                         |  |
| FIRMS Code                             | 4AN                       | 9-12            | M             | A Facilities Information and Resources Management System (FIRMS) Code representing the location of the goods.  |             |                    |           |                           |           |                    |           |      |           |                  |           |                     |           |                     |           |                      |           |                         |  |
| Status                                 | 1A                        | 13              | M             | A code of <i>A</i> indicates the status is active; a code of <i>D</i> indicates a deactivated status.  |             |                    |           |                           |           |                    |           |      |           |                  |           |                     |           |                     |           |                      |           |                         |  |
| Facility Type                          | 2N                        | 14-15           | M             | A code identifying the facility type. Valid Facility Type Codes are:<br><br><table border="0"> <thead> <tr> <th><b>Code</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td><b>01</b></td> <td>Container Freight Station</td> </tr> <tr> <td><b>02</b></td> <td>Foreign Trade Zone</td> </tr> <tr> <td><b>03</b></td> <td>Pier</td> </tr> <tr> <td><b>04</b></td> <td>Bonded Warehouse</td> </tr> <tr> <td><b>05</b></td> <td>Inspection Facility</td> </tr> <tr> <td><b>06</b></td> <td>Importer's Premises</td> </tr> <tr> <td><b>07</b></td> <td>Data Processing Site</td> </tr> <tr> <td><b>08</b></td> <td>CBP Administrative Site</td> </tr> </tbody> </table><br>Facilities with Type Code 07 or 08 should not be used for entry purposes. | <b>Code</b> | <b>Description</b> | <b>01</b> | Container Freight Station | <b>02</b> | Foreign Trade Zone | <b>03</b> | Pier | <b>04</b> | Bonded Warehouse | <b>05</b> | Inspection Facility | <b>06</b> | Importer's Premises | <b>07</b> | Data Processing Site | <b>08</b> | CBP Administrative Site |  |
| <b>Code</b>                            | <b>Description</b>        |                 |               |  |             |                    |           |                           |           |                    |           |      |           |                  |           |                     |           |                     |           |                      |           |                         |  |
| <b>01</b>                              | Container Freight Station |                 |               |  |             |                    |           |                           |           |                    |           |      |           |                  |           |                     |           |                     |           |                      |           |                         |  |
| <b>02</b>                              | Foreign Trade Zone        |                 |               |  |             |                    |           |                           |           |                    |           |      |           |                  |           |                     |           |                     |           |                      |           |                         |  |
| <b>03</b>                              | Pier                      |                 |               |  |             |                    |           |                           |           |                    |           |      |           |                  |           |                     |           |                     |           |                      |           |                         |  |
| <b>04</b>                              | Bonded Warehouse          |                 |               |  |             |                    |           |                           |           |                    |           |      |           |                  |           |                     |           |                     |           |                      |           |                         |  |
| <b>05</b>                              | Inspection Facility       |                 |               |  |             |                    |           |                           |           |                    |           |      |           |                  |           |                     |           |                     |           |                      |           |                         |  |
| <b>06</b>                              | Importer's Premises       |                 |               |  |             |                    |           |                           |           |                    |           |      |           |                  |           |                     |           |                     |           |                      |           |                         |  |
| <b>07</b>                              | Data Processing Site      |                 |               |  |             |                    |           |                           |           |                    |           |      |           |                  |           |                     |           |                     |           |                      |           |                         |  |
| <b>08</b>                              | CBP Administrative Site   |                 |               |  |             |                    |           |                           |           |                    |           |      |           |                  |           |                     |           |                     |           |                      |           |                         |  |
| Name of Facility                       | 35X                       | 16-50           | M             | The name of the facility where the goods are located.  |             |                    |           |                           |           |                    |           |      |           |                  |           |                     |           |                     |           |                      |           |                         |  |
| Last Update                            | 6N                        | 51-56           | M             | A numeric date in MMDDYY (month, day, year) format representing the last update.   |             |                    |           |                           |           |                    |           |      |           |                  |           |                     |           |                     |           |                      |           |                         |  |
| Filler                                 | 24AN                      | 57-80           | M             | Space fill.  |             |                    |           |                           |           |                    |           |      |           |                  |           |                     |           |                     |           |                      |           |                         |  |

## Record Identifier F311 (Output)

This is a conditional location of goods (FIRMS) file output record that provides data pertaining to the reference file code, facility address, city and state.

| <b>Record Identifier F311 (Output)</b> |                          |                 |               |  |             |
|--|--------------------------|-----------------|---------------|--|-------------|
| <b>Data Element</b>                    | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>   | <b>Note</b> |
| Control Identifier                     | 1A                       | 1               | M             | Must always equal F.   |             |
| Record Type                            | 1N                       | 2               | M             | Must always equal 3.   |             |
| Reference File Code                    | 2N                       | 3-4             | M             | Must always equal 11.  |             |
| Facility Address                       | 35X                      | 5-39            | M             | The street address or Post Office box number of the facility where the goods are located.  |             |
| City                                   | 35X                      | 40-74           | M             | The name of the city where the goods are located.  |             |
| State                                  | 2AN                      | 75-76           | M             | The United States Postal Service state abbreviation or Canadian province/territory where the goods are located. Valid Canadian Province/Territory Codes are:<br><br><b>Code Province/Territory</b><br><br><b>AB</b> Alberta<br><b>BC</b> British Columbia<br><b>MB</b> Manitoba<br><b>NB</b> New Brunswick<br><b>NL</b> Newfoundland (including Labrador)<br><b>NT</b> Northwest Territories<br><b>NS</b> Nova Scotia<br><b>ON</b> Ontario<br><b>PE</b> Prince Edward Island<br><b>PQ</b> Quebec<br><b>SK</b> Saskatchewan<br><b>YT</b> Yukon Territory<br><b>XV</b> Nunavut |             |
| Filler                                 | 4AN                      | 77-80           | M             | Space fill.  |             |

## Record Identifier F411 (Output)

This is a mandatory location of goods (FIRMS) output record that provides data pertaining to the ZIP code, country, error code and error message. Whenever the Automated Commercial System (ACS) edits and validations reject a FIRMS code query, the output includes Record Identifier F111 repeated exactly as it appeared on the input record followed by Record Identifier F411.

| <b>Record Identifier F411 (Output)</b> |                          |                 |               |  |             |
|--|--------------------------|-----------------|---------------|--|-------------|
| <b>Data Element</b>                    | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>   | <b>Note</b> |
| Control Identifier                     | 1A                       | 1               | M             | Must always equal F.   |             |
| Record Type                            | 1N                       | 2               | M             | Must always equal 4.   |             |
| Reference File Code                    | 2N                       | 3-4             | M             | Must always equal 11.  |             |
| ZIP Code                               | 9AN                      | 5-13            | C             | The United States Postal Service ZIP code identifying the area where the facility is located.                            |             |
| Country                                | 2A                       | 14-15           | C             | The International Organization for Standardization (ISO) country code. Valid ISO Country Codes are listed in Appendix B. |             |
| Filler                                 | 17AN                     | 16-32           | M             | Space fill.  |             |
| Error Code                             | 3AN                      | 33-35           | C             | A code identifying the error message.  |             |
| Error Message                          | 40X                      | 36-75           | C             | A narrative message providing the text of the error message.   |             |
| Filler                                 | 5AN                      | 76-80           | M             | Space fill.  |             |

## Record Identifier F112 (Input)

This is a conditional input record to query the import specialist team assignment file.

| <b>Record Identifier F112 (Input)</b> |                          |                 |               |  |             |
|---------------------------------------|--------------------------|-----------------|---------------|--|-------------|
| <b>Data Element</b>                   | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>   | <b>Note</b> |
| Control Identifier                    | 1A                       | 1               | M             | Must always equal F.   |             |
| Record Type                           | 1N                       | 2               | M             | Must always equal 1.   |             |
| Reference File<br>Code                | 2N                       | 3-4             | M             | Must always equal 12.  |             |
| District/Port Code                    | 4N                       | 5-8             | O             | Valid District/Port Codes can be queried through Record Identifier F101 of this chapter. |             |
| Filler                                | 72AN                     | 9-80            | M             | Space fill.  |             |

## Record Identifier F112 (Output)

This is a conditional output record that provides data pertaining to the import specialist team assignment file.

| <b>Record Identifier F112 (Output)</b> |                          |                 |               |   |             |
|--|--------------------------|-----------------|---------------|---|-------------|
| <b>Data Element</b>                    | <b>Length/<br/>Class</b> | <b>Position</b> | <b>Status</b> | <b>Description</b>  | <b>Note</b> |
| Control Identifier                     | 1A                       | 1               | M             | Must always equal F.  |             |
| Record Type                            | 1N                       | 2               | M             | Must always equal 1.  |             |
| Reference File Code                    | 2N                       | 3-4             | M             | Must always equal 12.   |             |
| District/Port Code                     | 4N                       | 5-8             | O             | Valid District/Port Codes can be queried through Record Identifier F101 of this chapter.  |             |
| Field Import Specialist Team No.       | 3N                       | 9-11            | M             | The assigned code of the field import specialist assigned to the tariff number.   |             |
| Tariff Number (1)                      | 10AN                     | 12-21           | C             | The first number in the range of tariff numbers assigned to the Field Import Specialist Team No.  |             |
| Tariff Number (2)                      | 10AN                     | 22-31           | C             | The last number in the range of tariff numbers assigned to the Field Import Specialist Team No.   |             |
| From Country Code                      | 4AN                      | 32-35           | C             | The first and lowest Schedule C number in the range identifying the country where the merchandise is imported from. Schedule C numbers are located in Annex A of the <i>Harmonized Tariff Schedule of the United States Annotated</i> . |             |
| To Country Code                        | 4AN                      | 36-39           | C             | The last and highest Schedule C number in the range identifying the country where the merchandise is imported from. Schedule C numbers are located in Annex A of the <i>Harmonized Tariff Schedule of the United States Annotated</i> . |             |
| Importer of Record Name                | 32AN                     | 40-71           | C             | The importer name in the SRE (Importer/Ultimate Consignee) file that corresponds to a related importer of record number in the Commodity Specialist Team Assignment file.   |             |
| Filler                                 | 9AN                      | 72-80           | M             | Space fill.   |             |