Appendix D

Metric Conversion

This appendix provides formulas to convert between inch-pound units and metric units.

With the adoption by the United States of the Harmonized Tariff Schedule (HTS) and its use of metric units, there will be a natural shift to report quantities on invoices in metric units. Where a need to convert exists, the following metric conversion factors should be used. These factors have been taken from the Federal Standard 376A, a Government-wide standard developed through the Government's Interagency Committee on Metric Policy.

The following chart provides the multiplier to be used in converting from inch-pound units to metric units. Where there is a need to convert from metric units to inch-pound units, divide rather than multiply by the factor.

Metric Conversion				
Quantity	From Inch-Pound Units	To Metric Units	Multiply By	
Mass	Ton (Long)	T (Metric Ton)(IT = 1,000 Kg.	1.016 047	
	Ton (Short)	T (Metric Ton)	0.907 184 74	
	Lb (Avdo)	Kg	0.453 592 37	
	Oz (Troy)	G	31.103 48	
Length	Yd	М	0.914 4	
	Ft	М	0.304 8	
	In	Cm	2.54	
	In	Mm	25.4	
Area	Yd2	M2	0.836 127 4	
	Ft2	M2	0.092 903 04	
	In2	Cm2	6.451 6	
	In2	Mm2	645.16	

Metric Conversion				
Quantity	From Inch-Pound Units	To Metric Units	Multiply By	
Volume	Yd3	M3	0.764 554 9	
	Bbl (Oil)	M3	0.158 987 3	
	(42 Gallons)		0.028 316 85	
	Ft3	M3		
	Ft3	L	28.316 85	
	Gal (Liq)	L	3.785 412	
	Quart (Liq)	L	0.946 352 9	
	Pint (Liq)	L	0.473 176 5	
	Fl Oz	Ml	29. 573 53	
	In3	Cm3		
Frequency	C/S (Formerly Cos. Cycles Per Second)	Hz	1.0	
Force	Кір	kN	4.448 222	
Radioactivity	Curie	MBq (Bq-becquerel)	37 000	
Stress	Lbf/In2 (formerly PSI)	MPa	0.006 894 757	
	Lbf/In2 (formerly PSI)	КРа	6.894 757	
Power	Btu/S	kW	1.055 056	
	hp (electric)	kW	0.746	
	Btu/H	W	0.293 071 1	
Celsius	°F	°C	$t^{o}C = (t^{o}F 32)/1.8$	

Note: The following conversion procedure should be followed for beverages, spirits and vinegar classified in Chapter 22 of the Harmonized Tariff Schedule of the United States Annotated (HTS): Multiply the number of proof-liters by 0.264172 to obtain proof-gallons at 15.56ÉC (60.F). For wine, multiply the number of proof-liters by 0.26417. This allows for the calculation of the U. S. excise tax.

Refer to Appendix C for a list of the Unit of Measure Codes.